



UVA 151 UV PROTECTION

INTERNAL INSTALLATION



DESCRIPTION

The UVA 151 colourless protection film delays the harmful effects of ultraviolet A without reducing the brightness of your room or window. It reduces the discolouration caused by solar radiation through shop windows, museums and art galleries so that delicate objects, jewellery or clothing are not damaged.





Durability: 12 to 15 years for a vertical application in Central Europe.



Use: for all types of glass.



Maintenance: after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



Storage: 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

INFORMATION

MATERIAL:	PET
ADHESIVE :	Acrylic polymer 13 gr/m ²
LINER:	Siliconized PET 23 microns
THICKNESS:	36 microns
UV BLOCKING:	99 %
COLOR:	Incolor
APPLICATION SIDE:	Internal
	min, + 5°C
STANDARDS:	EUROCLASSES
FIRE RANTING:	B-s1,d0
GUARANTEE:	10 Years inside*

^{*} For glazing not exposed to the sun

DIMENSIONS

By roll:



1,52 x

10 m 30 m

Application





Video of the installation





Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.